

- Pure sine wave solar inverter
- Selectable high power charging current
- Wide DC input range
- Selectable input voltage range for home appliances and personal computers
- Configurable AC/Solar input priority via LCD setting
- Compatible to mains voltage or generator power
- Auto restart while AC is recovering
- Overload and short circuit protection
- Smart battery charger design for optimized battery performance
- Cold start function



SAVIOR SOLAR V Specification

MODEL	SSVP 3000-24	SSVM 3000-24	SSVM-3000-24 Plus	SSVP 5000-48	SSVM5000-48
Rated Power	3000VA/2400W			5000VA/4000W	
INPUT					
Voltage	230 VAC				
Selectable Voltage Range	170-280 VAC (For Personal Computers) 90-280 VAC (For Home Appliances)				
Frequency Range	50 Hz/60 Hz (Auto sensing)				
OUTPUT					
AC Voltage Regulation (Batt. Mode)	230VAC ± 5%				
Surge Power	6000VA			10000VA	
Efficiency (Peak)	90% – 93%				
Transfer Time	10 ms (For Personal Computers) 20 ms (For Home Appliances)				
Waveform	Pure sine wave				
BATTERY					
Battery Voltage	24 VDC			48 VDC	
Floating Charge Voltage	27 VDC			54 VDC	
Overcharge Protection	32 VDC			63 VDC	
SOLAR CHARGER & AC CHARGER					
Solar Charger Type	PWM		MPPT		
Maximum PV Array Open Circuit Voltage	75 VDC	100 VDC	145 VDC	105 VDC	145 VDC
Maximum Solar Charge Current	50A	40A	60A	50A	60A
Maximum AC Charge Current	25A			60A	
Maximum Charge Current	70A	60A	120A	110A	120A
PHYSICAL					
Dimension, D X W X H (mm)	285 x 334 x 100			300 x 440 x 100	
Net Weight (kgs)	6.4Kg	6.6Kg	11Kg	11Kg	13Kg
Communication Interface	USB				
OPERATING ENVIRONMENT					
Humidity	5% to 95% Relative Humidity(Non-condensing)				
Operating Temperature	-10°C to 55°C				
Storage Temperature	-15°C to 60°C				

* Product specifications are subject to change without further notice



www.saviorsolar.com.tr
 SAVIOR KONTROL OTOMASYON SİSTEMLERİ
 ELEKTRONİK SANAYİ VE TİCARET A.Ş.
 Des Sanayi Sitesi 102 Sokak B-06 Blok No:6-8 34776
 Yukarı Dudulu / Ümraniye / İstanbul-Türkiye
 bilgi@saviorsolar.com.tr / tel : +90 216 466 36 83 (pbx) / faks : +90 216 466 36 85