

EMC TEST REPORT
For

SHENZHEN SUNRAY POWER CO., LTD

Inverter

Model No.: MPS-V-3200-24, MPS-V-5000-48

Prepared for : SHENZHEN SUNRAY POWER CO., LTD
Address : B16, Rd No.1, the 1st industry park, Guangming,
Shenzhen, Guangdong, China., 518107

Prepared by : EMTEK (SHENZHEN) CO., LTD.
Address : Bldg 69, Majialong Industry Zone,
Nanshan District, Shenzhen, Guangdong, China

Tel: (0755) 26954280

Fax: (0755) 26954282

Report Number : ES190523009E-1
Date of Test : May 24, 2018 to June 01, 2018
Date of Report : June 24, 2018

TABLE OF CONTENT

Test Report Description	Page
1.SUMMARY OF TEST RESULTS	7
2.GENERAL INFORMATION.....	8
2.1. Description of Device (EUT)	8
2.2. Description of Test Facility	8
2.3. Description of Support Device	9
2.4. Measurement Uncertainty	9
3.MEASURING DEVICE AND TEST EQUIPMENT.....	10
3.1. For Power Line Conducted Emission Measurement	10
3.2. For Radiated Emission Measurement	10
3.3. For Harmonic Current / Flicker Measurement	10
3.4. For Electrostatic Discharge Immunity Test	10
3.5. For RF Strength Susceptibility Test	11
3.6. For Electrical Fast Transient / Burst Immunity Test	11
3.7. For Surge Immunity Test.....	11
3.8. For Injected Current Susceptibility Test.....	11
3.9. For Magnetic Field Immunity Test.....	12
3.10. For Voltage Dips and Interruptions Test	12
4.POWER LINE CONDUCTED EMISSION MEASUREMENT.....	13
4.1. Block Diagram of Test Setup	13
4.2. Measuring Standard.....	13
4.3. Power Line Conducted Emission Limits	13
4.4. EUT Configuration of Measurement	13
4.5. Operating Condition of EUT	13
4.6. Test Procedure.....	14
4.7. Measuring Results	14
5.RADIATED EMISSION MEASUREMENT	19
5.1. Block Diagram of Test Setup	19
5.2. Measuring Standard.....	19
5.3. Radiated Emission Limits	19
5.4. EUT Configuration of Measurement	19
5.5. Operating Condition of EUT	20
5.6. Test Procedure.....	20
5.7. Measuring Results	20
6.HARMONIC CURRENT EMISSION MEASUREMENT	25
6.1. Block Diagram of Test Setup	25
6.2. Measuring Standard.....	25
6.3. Operation Condition of EUT	25
6.4. Measuring Results	25
7.VOLTAGE FLUCTUATION AND FLICKER MEASUREMENT	29
7.1. Block Diagram of Test Setup	29
7.2. Measuring Standard.....	29
7.3. Operation Condition of EUT	29
7.4. Measuring Results	29
8.IMMUNITY PERFORMANCE CRITERIA DESCRIPTION.....	31
9.ELECTROSTATIC DISCHARGE IMMUNITY TEST	32
9.1. Block Diagram of Test Setup	32

9.2. Test Standard	32
9.3. Severity Levels and Performance Criterion	32
9.4. Operating Condition of EUT	32
9.5. Test Procedure.....	33
9.6. Test Results	33
10. RF FIELD STRENGTH SUSCEPTIBILITY TEST	35
10.1. Block Diagram of Test Setup	35
10.2. Test Standard	35
10.3. Severity Levels and Performance Criterion	35
10.4. Operating Condition of EUT	35
10.5. Test Procedure.....	36
10.6. Test Results	36
11. ELECTRICAL FAST TRANSIENT/BURST IMMUNITY TEST.....	39
11.1. Block Diagram of Test Setup	39
11.2. Test Standard	39
11.3. Severity Levels and Performance Criterion	39
11.4. Operating Condition of EUT	39
11.5. Test Procedure.....	40
11.6. Test Results	40
12. SURGE IMMUNITY TEST	42
12.1. Block Diagram of Test Setup	42
12.2. Test Standard	42
12.3. Severity Levels and Performance Criterion	42
12.4. Operating Condition of EUT	42
12.5. Test Procedure.....	42
12.6. Test Results	43
13. INJECTED CURRENTS SUSCEPTIBILITY TEST	45
13.1. Block Diagram of Test Setup	45
13.2. Test Standard	45
13.3. Severity Levels and Performance Criterion	45
13.4. Operating Condition of EUT	45
13.5. Test Procedure.....	46
13.6. Test Results	46
14. MAGNETIC FIELD SUSCEPTIBILITY TEST.....	48
14.1. Block Diagram of Test Setup	48
14.2. Test Standard	48
14.3. Severity Levels and Performance Criterion	48
14.4. Operating Condition of EUT	49
14.5. Test Procedure.....	49
14.6. Test Results	49
15. VOLTAGE DIPS AND INTERRUPTIONS TEST	51
15.1. Block Diagram of Test Setup	51
15.2. Test Standard	51
15.3. Severity Levels and Performance Criterion	51
15.4. Operating Condition of EUT	51
15.5. Test Procedure.....	51
15.6. Test Results	51
16. PHOTOGRAPHS.....	53
16.1. Photos of Conducted Emission Measurement	53
16.2. Photos of Radiation Emission Measurement	54
16.3. Photo of Harmonic / Flicker Measurement	55
16.4. Photo of Electrostatic Discharge Test.....	55
16.5. Photo of RF Field Strength Susceptibility Test	56
16.6. Photo of Electrical Fast Transient / Burst Test.....	56
16.7. Photo of Surge Test	57
16.8. Photo of Injected Currents Susceptibility Test	57

16.9. Photo of Magnetic Field Immunity Test..... 58

16.10. Photo of Voltage Dips and Interruption Immunity Test 58

APPENDIX (Photos of EUT)

TEST REPORT DESCRIPTION

Applicant : SHENZHEN SUNRAY POWER CO., LTD
Manufacturer : SHENZHEN NEXT POWER TECHNOLOGY CO., LTD
Trade Mark : 
EUT : Inverter
Model No. : MPS-V-3200-24, MPS-V-5000-48
Power Supply : DC 360V for PV port, DC 24V for battery(MPS-V-3200-24), DC 48V for battery(MPS-V-5000-48), AC 230V/50Hz


Measurement Procedure Used:


EN 61000-6-3:2007+A1:2011+ AC:2012,
EN 61000-3-11: 2000,
EN 61000-3-12: 2011,
EN 61000-6-1:2007
(IEC 61000-4-2:2008, IEC 61000-4-3:2006+A1:2007+A2:2010, IEC61000-4-4:2012,
IEC 61000-4-5:2014, IEC 61000-4-6:2013, IEC 61000-4-8:2009, IEC 61000-4-11:2004)

The device described above is tested by EMTEK (SHENZHEN) CO., LTD. to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The measurement results are contained in this test report and EMTEK (SHENZHEN) CO., LTD. is assumed full of responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT (Equipment Under Test) is technically compliant with the EN61000-6-3, EN61000-3-2, EN61000-3-3 and EN61000-6-1 requirements.

This report applies to above tested sample only and shall not be reproduced in part without written approval of EMTEK (SHENZHEN) CO., LTD.

Date of Test : May 23, 2019 to June 21, 2019

Prepared by : 
Winmy Huang/Editor

Reviewer : 
Jessie Hu /Supervisor

Approved & Authorized Signer : 
Lisa Wang/Manager



Modified Information

Version	Report No.	Revision Date	Summary
Ver.1.0	ES190523009E	/	Original Report
Ver.1.1	ES190523009E-1	/	Change Applicant to SHENZHEN SUNRAY POWER CO., LTD Change model No. to MPS-V-3200-24, MPS-V-5000-48 Change trade mark to 

1. SUMMARY OF TEST RESULTS

EMISSION			
Description of Test Item	Standard	Limits	Results
Conducted Disturbance at Mains Terminals	EN 61000-6-3:2007+A1:2011 + AC:2012	--	Pass
Radiated Disturbance	EN 61000-6-3:2007+A1:2011 + AC:2012	--	Pass
Voltage Fluctuation and Flicker	EN 61000-3-11: 2000	Section 5	Pass
Harmonic Current Emissions	EN 61000-3-12: 2011	Table 2	Pass
IMMUNITY (EN 61000-6-1:2007)			
Description of Test Item	Basic Standard	Performance Criteria	Results
Electrostatic Discharge (ESD)	IEC 61000-4-2:2008	B	Pass
Radio-Frequency, Continuous Radiated Disturbance	IEC 61000-4-3:2006+A1:2007 +A2:2010	A	Pass
EFT/B Immunity	IEC61000-4-4:2012	B	Pass
Surge Immunity	IEC 61000-4-5:2014	B	Pass
Conducted RF Immunity	IEC 61000-4-6:2013	A	Pass
Power Frequency Magnetic Field	IEC 61000-4-8:2009	A	Pass
Voltage Dips, >95% Reduction	IEC 61000-4-11:2004	B	Pass
Voltage Dips, 30% Reduction		C	Pass
Voltage Interruptions		C	Pass
Note: N/A is an abbreviation for Not Applicable.			

2. GENERAL INFORMATION

2.1. Description of Device (EUT)

EUT	: Inverter
Model Number	: MPS-V-3200-24, MPS-V-5000-48 (Note: Two models are identical in circuitry and electrical, mechanical and physical construction; the only difference is the power derating of MPS-V-3200-24. We prepare MPS-V-3200-24, MPS-V-5000-48 for emission test, MPS-V-5000-48 for immunity test)
Test Voltage	: DC 360V for PV port, DC 24V for battery(MPS-V-3200-24), DC 48V for battery(MPS-V-5000-48), AC 230V/50Hz
Applicant	: SHENZHEN SUNRAY POWER CO., LTD
Address	: B16, Rd No.1, the 1st industry park, Guangming, Shenzhen, Guangdong, China., 518107
Manufacturer	: SHENZHEN NEXT POWER TECHNOLOGY CO., LTD
Address	: 13/F, Block B, Dadan Industrial Park, No. 503, JiHua Rd, LongGang District, Shenzhen, China, 518129
Date of Received	: May 23, 2019
Date of Test	: May 23, 2019 to June 21, 2019

2.2. Description of Test Facility

Site Description EMC Lab.	: Accredited by CNAS, 2016.10.24 The certificate is valid until 2022.10.28 The Laboratory has been assessed and proved to be in compliance with CNAS-CL01:2006 (identical to ISO/IEC 17025:2005) The Certificate Registration Number is L2291. Accredited by TUV Rheinland Shenzhen 2018.3.30 The Laboratory has been assessed according to the requirements ISO/IEC 17025. Accredited by FCC, August 06, 2018 Designation Number: CN1204 Test Firm Registration Number: 882943 Accredited by Industry Canada, November 09, 2018 The Certificate Registration Number is CN0008. Accredited by A2LA, August 08, 2018 The Certificate Number is 4321.01
Name of Firm	: EMTEK (SHENZHEN) CO., LTD.
Site Location	: Bldg 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, China

2.3. Description of Support Device

N/A : N/A

2.4. Measurement Uncertainty

Test Item	Uncertainty
Conducted Emission Uncertainty	: 3.16dB(9k~150kHz Conduction 2#) 2.90dB(150k-30MHz Conduction 2#)
Radiated Emission Uncertainty (3m Chamber)	: 3.78dB (30M~1GHz Polarize: H) 4.27dB (30M~1GHz Polarize: V)
Uncertainty for Flicker test	: 0.07%
Uncertainty for Harmonic test	: 1.8%
Uncertainty for C/S Test	: 1.45(Using CDN Test)
Uncertainty for R/S Test	: 2.10dB(80MHz-200MHz)
Uncertainty for test site temperature and humidity	: 0.6℃ 4%

3. MEASURING DEVICE AND TEST EQUIPMENT

3.1. For Power Line Conducted Emission Measurement

Used	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
☒	Test Receiver	Rohde & Schwarz	ESCS30	828985/018	May 20, 2019	1 Year
☒	L.I.S.N.	ROHDE & SCHWARZ	ESH3-Z5	100191	May 19, 2019	1 Year
☒	50Ω Coaxial Switch	Anritsu	MP59B	M20531	May 20, 2019	1 Year
☒	Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100006	May 19, 2019	1 Year

3.2. For Radiated Emission Measurement

Used	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
☒	EMI Test Receiver	Rohde & Schwarz	ESCI	101414	May 19, 2019	1 Year
☒	Pre-Amplifier	LUNAR-EM	LNA30M3G-25	J10100000071	May 19, 2019	1 Year
☒	Bilog Antenna	Schwarzbeck	VULB9163	660	May 20, 2019	1 Year
☒	Cable	H+B	NmSm-05-C15052	N/A	May 20, 2019	1 Year
☒	Cable	H+B	NmSm-2-C15201	N/A	May 20, 2019	1 Year
☒	Cable	H+B	NmNm-7-C15702	N/A	May 20, 2019	1 Year

3.3. For Harmonic Current / Flicker Measurement

Used	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
☒	45KVA AC Power source	Teseq	NSG 1007-45/45KVA	1305A02873	May 19, 2019	1 Year
☒	Signal conditioning Unit	Teseq	CCN 1000-3	1305A02873	May 19, 2019	1 Year
☒	Three phase impedance network	Teseq/Germany	INA2197/37A	1305A02873	N/A	N/A
☒	Three phase impedance network	Teseq/Germany	INA 2196/75A	1305A02874	N/A	N/A
☐	Proflin 2100 AC Switching Unit	Teseq/Germany	NSG2200-3	A22714	N/A	N/A

3.4. For Electrostatic Discharge Immunity Test

Used	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
☒	ESD Tester	TESEQ AG	NSG 438A	130	May 20, 2019	1 Year
☒	Impulse Module	TESEQ AG	INA 4380-150pF/3 30Ohm	403-550/1712	May 20, 2019	1 Year

3.5. For RF Strength Susceptibility Test

Used	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
☒	Signal Generator	Agilent	N5181A	MY50145187	May 19, 2019	1 Year
☒	RF Power Meter. Dual Channel	BOONTON	4232A	10539	May 20, 2019	1 Year
☒	50ohm Diode Power Sensor	BOONTON	51011EMC	34236/34238	May 20, 2019	1 Year
☒	Field Strength Meter	DARE	RSS1006A	10I00037S O22	May 20, 2019	1 Year
☒	50ohm Diode Power Sensor	BOONTON	51011EMC	36164	May 20, 2019	1 Year
☒	Power Amplifier	MILMEGA	80RF1000-175	1059345	May 19, 2019	1 Year
☒	Power Amplifier	MILMEGA	AS0102-55	1018770	May 19, 2019	1 Year
☒	Power Amplifier	MILMEGA	AS1860-50	1059346	May 19, 2019	1 Year
☒	Log.-Per. Antenna	SCHWARZBECK	VULP 9118E	811	May 20, 2019	1 Year
☒	Broad-Band Horn Antenna	SCHWARZBECK	STLP 9149	9149-227	May 20, 2019	1 Year
☒	Multi-function interface system	DARE	CTR1009B	12I00250S NO72	N/A	N/A
☒	Automatic switch group	DARE	RSW1004A	N/A	N/A	N/A

3.6. For Electrical Fast Transient / Burst Immunity Test

Used	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
☒	Burst Tester	HAEFELY	PEFT4010	080981-16	May 20, 2019	1 Year
☐	Coupling Clamp	HAEFELY	IP-4A	147147	May 20, 2019	1 Year

3.7. For Surge Immunity Test

Used	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
☒	Surge Controller	HAEFELY	Psurge 8000	174031	May 20, 2019	1 Year
☒	Impulse Module	HAEFELY	PIM 100	174124	May 20, 2019	1 Year
☒	Coupling Decoupling Filter	HAEFELY	PCD 130	172181	May 20, 2019	1 Year
☐	Coupling Module	HAEFELY	PCD122	174354	May 20, 2019	1 Year
☐	Surge Impulse Module	HAEFELY	PIM 120	174435	May 20, 2019	1 Year
☐	Coupling Module	HAEFELY	PCD 126A	174387	May 20, 2019	1 Year
☐	Impulse Module	HAEFELY	PIM 110	174391	May 20, 2019	1 Year

3.8. For Injected Current Susceptibility Test

Used	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
☒	Simulator	EMTEST	CWS500C	0900-12	May 20, 2019	1 Year
☒	CDN	EMTEST	CDN-M2	5100100100	May 20, 2019	1 Year
☐	CDN	EMTEST	CDN-M3	0900-11	May 20, 2019	1 Year
☐	Injection Clamp	EMTEST	F-2031-23MM	368	May 20, 2019	1 Year
☒	Attenuator	EMTEST	ATT6	0010222A	May 20, 2019	1 Year

3.9. For Magnetic Field Immunity Test


Used	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
☒	Magnetic Field Tester	HAEFELY	MAG100	250040.1	May 19, 2019	1 Year

3.10. For Voltage Dips and Interruptions Test

Used	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
☒	45KVA AC Power source	Teseq	NSG 1007-45/45K VA	1305A02873	May 19, 2019	1 Year
☐	Signal conditioning Unit	Teseq	CCN 1000-3	1305A02873	May 19, 2019	1 Year
☐	Three phase impedance network	Teseq/Germany	INA2197/37A	1305A02873	N/A	N/A
☐	Three phase impedance network	Teseq/Germany	INA 2196/75A	1305A02874	N/A	N/A
☒	Proflin 2100 AC Switching Unit	Teseq/Germany	NSG2200-3	A22714	N/A	N/A

4. POWER LINE CONDUCTED EMISSION MEASUREMENT

4.1. Block Diagram of Test Setup



LISN: Artificial Mains Network
AE: Associated equipment
EUT: Equipment under test

4.2. Measuring Standard

EN 61000-6-3:2007+A1:2011+ AC:2012

4.3. Power Line Conducted Emission Limits

Frequency (MHz)	Limit (dB μ V)	
	Quasi-peak Level	Average Level
0.15 ~ 0.50	66.0 ~ 56.0 *	56.0 ~ 46.0 *
0.50 ~ 5.00	56.0	46.0
5.00 ~ 30.00	60.0	50.0

NOTE1-The lower limit shall apply at the transition frequencies.
NOTE2-The limit decreases linearly with the logarithm of the frequency in the range 0.15MHz to 0.50MHz.

4.4. EUT Configuration of Measurement

The following equipments are installed on Conducted Emission Measurement to meet EN 61000-6-3 requirements and operating in a manner which tends to maximize its emission characteristics in a normal application.

EUT : Inverter
Model Number : MPS-V-3200-24, MPS-V-5000-48

4.5. Operating Condition of EUT

4.5.1. Setup the EUT as shown on Section 4.1.

4.5.2. Turn on the power of all equipment.

4.5.3. Let the EUT work in measuring mode (AC Charge Mode) and measure it.

4.6. Test Procedure

The EUT is put on the plane 0.8m high above the ground by insulating support and connected to the AC mains through Line Impedance Stability Network (L.I.S.N). This provided a 50ohm coupling impedance for the tested equipments. Both sides of AC line are investigated to find out the maximum conducted emission according to the EN61000-6-3 regulations during conducted emission measurement.

The bandwidth of the field strength meter (R&S Test Receiver) is set at 9kHz in 150kHz~30MHz and 200Hz in 9kHz~150kHz.

The frequency range from 150kHz to 30MHz is investigated.

All the scanning waveform is put in the following pages.


4.7. Measuring Results

PASS.

Please reference to the following pages.

Conducted Emission Measurement

File :naisite Data :#25 Date: 2019/06/14 Time: 16:46:47



Site Conduction #2

Phase: **L1**

Temperature: 23.7

Limit: (CE)EN61000-6-3_QP

Power: AC 230V/50Hz

Humidity: 41 %

Mode:AC Charge Mode

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1	*	0.1500	48.56	9.89	58.45	66.00	-7.55	QP	
2		0.1500	36.29	9.89	46.18	56.00	-9.82	AVG	
3		0.1620	39.00	9.90	48.90	65.36	-16.46	QP	
4		0.1620	29.58	9.90	39.48	55.36	-15.88	AVG	
5		0.1980	36.46	9.90	46.36	63.69	-17.33	QP	
6		0.1980	28.01	9.90	37.91	53.69	-15.78	AVG	
7		0.2820	25.76	9.91	35.67	60.76	-25.09	QP	
8		0.2820	16.80	9.91	26.71	50.76	-24.05	AVG	
9		7.6460	33.70	9.99	43.69	60.00	-16.31	QP	
10		7.6460	24.84	9.99	34.83	50.00	-15.17	AVG	
11		28.8860	22.35	10.30	32.65	60.00	-27.35	QP	
12		28.8860	14.06	10.30	24.36	50.00	-25.64	AVG	

*:Maximum data x:Over limit !:over margin Comment: Factor build in receiver. Operator: XZC


Conducted Emission Measurement

File : naisite
100.0 dBuV

Data : #24

Date: 2019/06/14

Time: 16:45:06



Site Conduction #2

Phase: N

Temperature: 23.7

Limit: (CE)EN61000-6-3_QP

Power: AC 230V/50Hz

Humidity: 41 %

Mode: AC Charge Mode

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1	*	0.1500	48.31	9.89	58.20	66.00	-7.80	QP	
2		0.1500	35.82	9.89	45.71	56.00	-10.29	AVG	
3		0.2020	36.28	9.90	46.18	63.53	-17.35	QP	
4		0.2020	27.72	9.90	37.62	53.53	-15.91	AVG	
5		0.2820	25.15	9.91	35.06	60.76	-25.70	QP	
6		0.2820	16.45	9.91	26.36	50.76	-24.40	AVG	
7		2.8820	22.39	9.94	32.33	56.00	-23.67	QP	
8		2.8820	10.16	9.94	20.10	46.00	-25.90	AVG	
9		7.6020	38.88	9.99	48.87	60.00	-11.13	QP	
10		7.6020	28.93	9.99	38.92	50.00	-11.08	AVG	
11		28.5980	22.66	10.30	32.96	60.00	-27.04	QP	
12		28.5980	14.47	10.30	24.77	50.00	-25.23	AVG	

*:Maximum data x:Over limit !:over margin Comment: Factor build in receiver. Operator: XZC

Conducted Emission Measurement


File :naisite

Data :#26

Date: 2019/06/14

Time: 16:50:45

100.0 dBuV



Site: Conduction #2

Phase: L1

Temperature: 23.7

Limit: (CE)EN61000-6-3_QP

Power: AC 230V/50Hz

Humidity: 41 %

Mode: AC Charge Mode


Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.1500	44.79	9.89	54.68	66.00	-11.32	QP	
2	*	0.1500	39.86	9.89	49.75	56.00	-6.25	AVG	
3		0.1620	41.92	9.90	51.82	65.36	-13.54	QP	
4		0.1620	29.52	9.90	39.42	55.36	-15.94	AVG	
5		0.1980	41.51	9.90	51.41	63.69	-12.28	QP	
6		0.1980	35.45	9.90	45.35	53.69	-8.34	AVG	
7		0.2820	28.16	9.91	38.07	60.76	-22.69	QP	
8		0.2820	16.88	9.91	26.79	50.76	-23.97	AVG	
9		7.6420	36.42	9.99	46.41	60.00	-13.59	QP	
10		7.6420	26.94	9.99	36.93	50.00	-13.07	AVG	
11		29.6060	23.67	10.31	33.98	60.00	-26.02	QP	
12		29.6060	15.53	10.31	25.84	50.00	-24.16	AVG	

*:Maximum data x:Over limit !:over margin Comment: Factor build in receiver. Operator: XZC

Conducted Emission Measurement

File : naisite Data : #27 Date: 2019/06/14 Time: 16:52:56



Site Conduction #2

Phase: N

Temperature: 23.7

Limit: (CE)EN61000-6-3_QP

Power: AC 230V/50Hz

Humidity: 41 %

Mode: AC Charge Mode


Note:

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over		
		MHz	Level	Factor	ment			Detector	Comment
			dBuV	dB	dBuV	dBuV	dB		
1		0.1620	45.80	9.90	55.70	65.36	-9.66	QP	
2	*	0.1620	38.40	9.90	48.30	55.36	-7.06	AVG	
3		0.1980	43.82	9.90	53.72	63.69	-9.97	QP	
4		0.1980	33.42	9.90	43.32	53.69	-10.37	AVG	
5		0.2820	26.51	9.91	36.42	60.76	-24.34	QP	
6		0.2820	16.71	9.91	26.62	50.76	-24.14	AVG	
7		7.7580	38.66	10.00	48.66	60.00	-11.34	QP	
8		7.7580	30.20	10.00	40.20	50.00	-9.80	AVG	
9		11.4820	20.19	10.02	30.21	60.00	-29.79	QP	
10		11.4820	12.18	10.02	22.20	50.00	-27.80	AVG	
11		28.6860	23.23	10.30	33.53	60.00	-26.47	QP	
12		28.6860	15.29	10.30	25.59	50.00	-24.41	AVG	

*:Maximum data x:Over limit !:over margin Comment: Factor build in receiver. Operator: XZC

5. RADIATED EMISSION MEASUREMENT

5.1. Block Diagram of Test Setup



5.2. Measuring Standard

EN 61000-6-3:2007+A1:2011+ AC:2012

5.3. Radiated Emission Limits

FREQUENCY (MHz)	DISTANCE (Meters)	FIELD STRENGTHS LIMIT (dB μ V/m)
30 ~ 230	10	30
230 ~ 1000	10	37

Note: (1) The smaller limit shall apply at the combination point between two frequency bands.
(2) Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the EUT.

5.4. EUT Configuration of Measurement

The EN 61000-6-3 regulations test method must be used to find the maximum emission during radiated emission measurement.

EUT : Inverter
Model Number : MPS-V-3200-24, MPS-V-5000-48

5.5. Operating Condition of EUT

5.5.1. Setup the EUT as shown on Section 5.1.

5.5.2. Turn on the power of all equipment.

5.5.3. Let the EUT work in measuring mode (Inverter Mode, AC Charge Mode, Solar Charge Mode) and measure it.

5.6. Test Procedure

The EUT is placed on a turntable which is 0.8 meter high above the ground. The turntable can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 10 meters away from the receiving antenna that is mounted on an antenna tower. The antenna can be moved up and down from 1 to 4 meters to find out the maximum emission level. Bilog antenna (calibrated by Dipole Antenna) is used as a receiving antenna. Both horizontal and vertical polarization of the antenna is set on test.

The bandwidth of the Receiver (ESCI) is set at 120kHz.

5.7. Measuring Results

PASS.

All of the mode were tested, the data of the worst case are recorded in the following pages.

The frequency range from 30MHz to 1000MHz is investigated.

Please reference to the following pages.

Radiated Emission Measurement


File :NAISITE

Data :#24

Date: 2019/6/1

Time: 11:36:47

80.0 dBuV/m



Site 10m Chamber 1#

Polarization: **Horizontal**

Temperature: 26

Limit: (RE10M)EN61000-6-3

Power: 230V/50Hz

Humidity: 60 %

Mode:AC Charge Mode

Note:

No.	Mk.	Freq.	Reading Level	Ant. Factor	Pre Amp Gain	Cable loss	Measure-ment	Limit	Over		
		MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	!	30.1051	56.49	11.18	43.29	0.8	25.18	30.00	-4.82	QP	
2		38.2120	53.60	12.45	43.33	0.78	23.50	30.00	-6.50	QP	
3	!	54.8348	55.12	13.46	43.4	0.82	26.00	30.00	-4.00	QP	
4	*	61.9951	57.40	12.02	43.43	0.91	26.90	30.00	-3.10	QP	
5	!	70.0901	58.39	9.57	43.47	1.01	25.50	30.00	-4.50	QP	
6	!	82.9385	59.02	8.01	43.52	1.18	24.69	30.00	-5.31	QP	

*:Maximum data x:Over limit !:over margin

Operator:

Radiated Emission Measurement


File :NAISITE

Data :#25

Date: 2019/6/1

Time: 11:36:47

80.0 dBuV/m



Site 10m Chamber 1#

Polarization: **Vertical**

Temperature: 26

Limit: (RE10M)EN61000-6-3

Power: 230V/50Hz

Humidity: 60 %

Mode:AC Charge Mode

Note:

No.	Mk.	Freq.	Reading Level	Ant. Factor	Pre Amp Gain	Cable loss	Measure-ment	Limit	Over	Detector	Comment
		MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	!	30.1051	57.53	10.99	43.01	0.99	26.50	30.00	-3.50	QP	
2	*	32.6340	58.00	10.83	43.03	1	26.80	30.00	-3.20	QP	
3	!	41.8596	54.00	13.45	43.08	1.03	25.40	30.00	-4.60	QP	
4	!	53.8817	53.01	13.71	43.14	1.12	24.70	30.00	-5.30	QP	
5	!	92.4624	57.01	10.19	43.36	1.76	25.60	30.00	-4.40	QP	
6	!	97.7980	56.65	11.19	43.39	1.85	26.30	30.00	-3.70	QP	

*:Maximum data x:Over limit !:over margin

Operator:

Radiated Emission Measurement


File :NAISITE

Data :#18

Date: 2019/6/1

Time: 11:06:59

80.0 dBuV/m



Site 10m Chamber 1#

Polarization: **Horizontal**

Temperature: 26

Limit: (RE10M)EN61000-6-3

Power: 230V/50Hz

Humidity: 60 %

Mode:AC Charge Mode

Note:

No.	Mk.	Freq.	Reading	Ant.	Pre Amp	Cable	Measure-	Limit	Over		
		MHz	Level	Factor	Gain	loss	ment			Detector	Comment
			dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1		33.3280	54.21	11.5	43.3	0.79	23.20	30.00	-6.80	QP	
2		46.9948	52.39	13.7	43.36	0.77	23.50	30.00	-6.50	QP	
3	*	55.8046	56.06	13.41	43.4	0.83	26.90	30.00	-3.10	QP	
4	!	61.9951	57.10	12.02	43.43	0.91	26.60	30.00	-3.40	QP	
5	!	70.0903	58.89	9.57	43.47	1.01	26.00	30.00	-4.00	QP	
6		96.0986	54.02	11.22	43.58	1.34	23.00	30.00	-7.00	QP	

*:Maximum data x:Over limit !:over margin

Operator:

Radiated Emission Measurement


File :NAISITE

Data :#19

Date: 2019/6/1

Time: 11:07:00

80.0 dBuV/m



Site 10m Chamber 1#

Polarization: **Vertical**

Temperature: 26

Limit: (RE10M)EN61000-6-3

Power: 230V/50Hz

Humidity: 60 %

Mode:AC Charge Mode

Note:


No.	Mk.	Freq.	Reading Level	Ant. Factor	Pre Amp Gain	Cable loss	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	*	30.4237	58.06	10.96	43.01	0.99	27.00	30.00	-3.00	QP	
2	!	40.7014	55.13	13.05	43.07	1.03	26.14	30.00	-3.86	QP	
3	!	52.0251	52.74	13.8	43.13	1.09	24.50	30.00	-5.50	QP	
4	!	57.7961	56.41	12.47	43.17	1.19	26.90	30.00	-3.10	QP	
5	!	105.6414	56.39	11.56	43.39	1.94	26.50	30.00	-3.50	QP	
6	!	119.8555	57.35	9.83	43.36	2.08	25.90	30.00	-4.10	QP	

*:Maximum data x:Over limit !:over margin

Operator:

6. HARMONIC CURRENT EMISSION MEASUREMENT

6.1. Block Diagram of Test Setup



6.2. Measuring Standard

EN 61000-3-12: 2011 Table 2

6.3. Operation Condition of EUT

6.3.1. Setup the EUT as shown on Section 6.1.

6.3.2. Turn on the power of all equipment.

6.3.3. Let the EUT work in measuring mode (AC Charge Mode) and measure it.

6.4. Measuring Results

PASS.

Please see the attached page.


Harmonics – Per EN/IEC61000-3-12(Run time)

EUT: Inverter Tested by: LJX
 Test category: Table:2, Rsce=33, Inter-Harm, Test Margin: 100
 Test date: 2019/6/6 Start time: 9:53:13 End time: 9:56:06
 Test duration (min): 2.5 Data file name: WIN2106_H-000004.cts_data
 Comment: AC CHARGER MODE
 Customer: SHENZHEN SUNRAY POWER CO., LTD

Test Result: Pass


Source qualification: Normal

Current & voltage waveforms



Harmonics and Class 2 limit line

European Limits



Test result: Pass

Worst harmonic was #13 with 14.25 % of the limit.

Current Test Result Summary (Run time)

EUT: Inverter Tested by: LJX
 Test category: Table:2, Rsce=33, Inter-Harm, Test Margin: 100
 Test date: 2019/6/6 Start time: 9:53:13 End time: 9:56:06
 Test duration (min): 2.5 Data file name: WIN2106_H-000004.cts_data
 Comment: AC CHARGER MODE
 Customer: SHENZHEN SUNRAY POWER CO., LTD

Test Result: Pass Measured I-ref: 22.746 Amp rms Source: Normal
 I-THC(%): 0.8 Limit(%): 23.0 PWHC(%): 2.2 PWHC Limit(%): 23.0

Highest parameter values during test:

V_RMS (Volts):	230.00	Frequency(Hz):	50.00
I_Peak (Amps):	33.020	I_RMS (Amps):	22.762
I_Fund (Amps):	22.746	Crest Factor:	1.452
Power (Watts):	5218	Power Factor:	0.997

Harm#	Harms(avg)	100%Limit	%of Limit	Harms(max)	150%Limit	%of Limit	Status
2	0.008	1.820	0.4	0.011	2.730	0.4	Pass
3	0.076	4.913	1.5	0.085	7.370	1.2	Pass
4	0.004	0.910	N/A	0.005	1.365	N/A	Pass
5	0.068	2.434	2.8	0.071	3.651	1.9	Pass
6	0.003	0.607	N/A	0.004	0.910	N/A	Pass
7	0.047	1.638	2.9	0.049	2.457	2.0	Pass
8	0.003	0.455	N/A	0.004	0.682	N/A	Pass
9	0.073	0.864	8.5	0.075	1.297	5.8	Pass
10	0.003	0.364	N/A	0.003	0.546	N/A	Pass
11	0.037	0.705	5.3	0.039	1.058	3.7	Pass
12	0.003	0.303	N/A	0.004	0.455	N/A	Pass
13	0.064	0.455	14.2	0.065	0.682	9.6	Pass
14	0.003	N/A	N/A	0.003	N/A	N/A	N/A
15	0.029	N/A	N/A	0.030	N/A	N/A	N/A
16	0.004	N/A	N/A	0.005	N/A	N/A	N/A
17	0.053	N/A	N/A	0.053	N/A	N/A	N/A
18	0.007	N/A	N/A	0.007	N/A	N/A	N/A
19	0.027	N/A	N/A	0.029	N/A	N/A	N/A
20	0.005	N/A	N/A	0.006	N/A	N/A	N/A
21	0.039	N/A	N/A	0.040	N/A	N/A	N/A
22	0.005	N/A	N/A	0.006	N/A	N/A	N/A
23	0.027	N/A	N/A	0.028	N/A	N/A	N/A
24	0.007	N/A	N/A	0.008	N/A	N/A	N/A
25	0.025	N/A	N/A	0.026	N/A	N/A	N/A
26	0.005	N/A	N/A	0.005	N/A	N/A	N/A
27	0.030	N/A	N/A	0.030	N/A	N/A	N/A
28	0.004	N/A	N/A	0.004	N/A	N/A	N/A
29	0.012	N/A	N/A	0.013	N/A	N/A	N/A
30	0.003	N/A	N/A	0.004	N/A	N/A	N/A
31	0.028	N/A	N/A	0.029	N/A	N/A	N/A
32	0.003	N/A	N/A	0.004	N/A	N/A	N/A
33	0.009	N/A	N/A	0.010	N/A	N/A	N/A
34	0.004	N/A	N/A	0.004	N/A	N/A	N/A
35	0.025	N/A	N/A	0.025	N/A	N/A	N/A
36	0.004	N/A	N/A	0.004	N/A	N/A	N/A
37	0.017	N/A	N/A	0.018	N/A	N/A	N/A
38	0.003	N/A	N/A	0.004	N/A	N/A	N/A
39	0.020	N/A	N/A	0.021	N/A	N/A	N/A
40	0.004	N/A	N/A	0.005	N/A	N/A	N/A

Note: Measured I-ref was applied for this test.

Voltage Source Verification Data (Run time)

EUT: Inverter Tested by: LJX
 Test category: Table:2, Rsce=33, Inter-Harm, Test Margin: 100
 Test date: 2019/6/6 Start time: 9:53:13 End time: 9:56:06
 Test duration (min): 2.5 Data file name: WIN2106_H-000004.cts_data
 Comment: AC CHARGER MODE
 Customer: SHENZHEN SUNRAY POWER CO., LTD

Test Result: Pass Source qualification: Normal
 Measured source distortion is within the requirements of the standards
 Measurements are compliant with IEC/EN61000-3-12 Ed.2 (2011) & IEC/EN61000-4-7


Highest parameter values during test:

Voltage (Vrms): 230.00	Frequency(Hz): 50.00
I_Peak (Amps): 33.020	I_RMS (Amps): 22.762
I_Fund (Amps): 22.746	Crest Factor: 1.452
Power (Watts): 5218	Power Factor: 0.997

Harm#	Harmonics V-rms	Limit V-rms	% of Limit	Status
2	0.097	0.920	10.51	OK
3	0.163	2.875	5.66	OK
4	0.038	0.920	4.11	OK
5	0.115	3.449	3.33	OK
6	0.018	0.920	2.00	OK
7	0.139	2.875	4.85	OK
8	0.021	0.920	2.25	OK
9	0.177	1.380	12.84	OK
10	0.021	0.920	2.28	OK
11	0.141	1.610	8.75	OK
12	0.022	0.690	3.16	OK
13	0.154	1.380	11.16	OK
14	0.022	0.690	3.18	OK
15	0.143	0.690	20.73	OK
16	0.020	0.690	2.93	OK
17	0.129	0.690	18.69	OK
18	0.027	0.690	3.90	OK
19	0.122	0.690	17.74	OK
20	0.027	0.690	3.92	OK
21	0.108	0.690	15.63	OK
22	0.021	0.690	3.04	OK
23	0.126	0.690	18.23	OK
24	0.026	0.690	3.75	OK
25	0.085	0.690	12.27	OK
26	0.023	0.690	3.30	OK
27	0.110	0.690	15.96	OK
28	0.023	0.690	3.34	OK
29	0.076	0.690	11.02	OK
30	0.018	0.690	2.60	OK
31	0.090	0.690	13.08	OK
32	0.018	0.690	2.62	OK
33	0.069	0.690	9.97	OK
34	0.022	0.690	3.14	OK
35	0.073	0.690	10.52	OK
36	0.022	0.690	3.24	OK
37	0.075	0.690	10.92	OK
38	0.017	0.690	2.41	OK
39	0.059	0.690	8.50	OK
40	0.025	0.690	3.58	OK

7. VOLTAGE FLUCTUATION AND FLICKER MEASUREMENT

7.1. Block Diagram of Test Setup



7.2. Measuring Standard

EN 61000-3-11: 2000 Section 5

7.3. Operation Condition of EUT

7.3.1. Me Setup the EUT as shown on Section 7.1.

7.3.2. Turn on the power of all equipment.

7.3.3. Let the EUT work in measuring mode (AC Charge Mode) and measure it.

7.4. Measuring Results

PASS.

Please see the attached page.


Flicker Test Summary (Run time) per EN/IEC61000-3-11

EUT: Inverter
Test category: All parameters
Test date: 2019/6/6
Test duration (min): 10
Comment: AC CHARGING MODE
Customer: SHENZHEN SUNRAY POWER CO., LTD
Z-test = (0.400 + j 0.250 Ohm)


Tested by: LJX
Test Margin: 100
Start time: 10:00:13
End time: 10:10:44
Data file name: WIN2106_F-000005.cts_data

Test Result: Pass
Status: Test Completed

Pst_i and limit line



Plt and limit line



Parameter values recorded during the test:

Vrms at the end of test (Volt): 224.68

T-max (mS):	0.0	Test limit (mS):	500.0	Pass
Highest dc (%):	0.00	Test limit (%):	3.30	Pass
Highest dmax (%):	0.09	Test limit (%):	4.00	Pass
Highest Pst (10 min. period):	0.064	Test limit:	1.000	Pass
Highest Plt (2 hr. period):	0.028	Test limit:	0.650	Pass

Calculated dmax(%): 0.000
Calculated dc(%): 0.000
Calculated Pst : 0.064
Calculated Plt : 0.028

8. IMMUNITY PERFORMANCE CRITERIA DESCRIPTION

Performance Level

The test results shall be classified in terms of the loss of function or degradation of performance of the equipment under test, relative to a performance level by its manufacturer or the requestor of the test, or the agreed between the manufacturer and the purchaser of the product.

Definition related to the performance level:

1. Based on the used product standard
2. Based on the declaration of the manufacturer, requestor or purchaser

Criterion A:

The apparatus shall continue to operate as intended during and after the test. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer, when the apparatus is used as intended. The performance level may be replaced by a permissible loss of performance. If the minimum performance level or the permissible performance loss is not specified by the manufacturer, either of these may be derived from the product description and documentation and what the user may reasonably expect from the apparatus if used as intended.

Criterion B:


The apparatus shall continue to operate as intended after the test. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer, when the apparatus is used as intended. The performance level may be replaced by a permissible loss of performance. During the test, degradation of performance is however allowed. No change of actual operating state or stored data is allowed. If the minimum performance level or the permissible performance loss is not specified by the manufacturer, either of these may be derived from the product description and documentation and what the user may reasonably expect from the apparatus if used as intended.

Criterion C:

Temporary loss of function is allowed, provided the function is self-recoverable or can be restored by the operation of the controls.

9. ELECTROSTATIC DISCHARGE IMMUNITY TEST

9.1. Block Diagram of Test Setup



9.2. Test Standard

EN 61000-6-1:2007
(IEC 61000-4-2:2008 Severity Level: 3 / Air Discharge: $\pm 8\text{kV}$
Level: 2 / Contact Discharge: $\pm 4\text{kV}$)

9.3. Severity Levels and Performance Criterion

9.3.1. Severity level

Level	Test Voltage Contact Discharge (kV)	Test Voltage Air Discharge (kV)
1	± 2	± 2
2	± 4	± 4
3	± 6	± 8
4	± 8	± 15
X	Special	Special

9.3.2. Performance criterion: B

9.4. Operating Condition of EUT

9.4.1. Setup the EUT as shown on Section 9.1.

9.4.2. Turn on the power of all equipment.

9.4.3. Let the EUT work in test mode (Inverter Mode, AC Charge Mode, Solar Charge Mode) and test it.

9.5. Test Procedure

9.5.1. Air Discharge:

This test is done on a non-conductive surface. The round discharge tip of the discharge electrode shall be approached as fast as possible to touch the EUT. After each discharge, the discharge electrode shall be removed from the EUT. The generator is then re-triggered for a new single discharge and repeated 10 times for each pre-selected test point. This procedure shall be repeated until all the air discharge completed.

9.5.2. Contact Discharge:

All procedure shall be the same as Section 9.5.1. except that the tip of the discharge electrode shall touch the EUT before the discharge switch is operated.

9.5.3. Indirect discharge for horizontal coupling plane

At least 10 single discharges (in the most sensitive polarity) shall be applied at the front edge of each HCP opposite the center point of each unit (if applicable) of the EUT and 0.1m from the front of the EUT. The long axis of the discharge electrode shall be in the plane of the HCP and perpendicular to its front edge during the discharge.

9.5.4. Indirect discharge for vertical coupling plane

At least 10 singles discharge (in the most sensitive polarity) shall be applied to the center of one vertical edge of the coupling plane. The coupling plane, of dimensions 0.5m×0.5m, is placed parallel to, and positioned at a distance of 0.1m from the EUT. Discharges shall be applied to the coupling plane, with this plane in sufficient different positions that the four faces of the EUT are completely illuminated.

9.6. Test Results

PASS.

Please refer to the following page.


Electrostatic Discharge Test Result

EMTEK (SHENZHEN) CO., LTD.

Applicant	SHENZHEN SUNRAY POWER CO., LTD	
EUT	Inverter	Test Date : June 06, 2019
M/N	MPS-V-5000-48	Temperature : 24.9°C
Power Supply	DC 360V, DC 48V for battery, AC 230V/50Hz	Humidity : 48%
Air discharge	± 8.0kV	Test ode : Inverter Mode, AC Charge Mode, Solar Charge Mode
Contact discharge:	± 4.0kV	Criterion : B
Location	Kind A-Air Discharge C-Contact Discharge	Result
Screw	C	A
Metal	C	A
Button	A	A
Screen	A	A
Slot	A	A
USB	A	A
HCP	C	A
VCP of front	C	A
VCP of rear	C	A
VCP of left	C	A
VCP of right	C	A
Note:		

10. RF FIELD STRENGTH SUSCEPTIBILITY TEST

10.1. Block Diagram of Test Setup



10.2. Test Standard

EN 61000-6-1:2007

(IEC 61000-4-3:2006+A1:2007+A2:2010, Severity Level: 1V/m, 3V/m)

10.3. Severity Levels and Performance Criterion

10.3.1. Severity Levels

Level	Field Strength V/m
1.	1
2.	3
3.	10
X	Special

10.3.2. Performance Criterion: A

10.4. Operating Condition of EUT

10.4.1. Me Setup the EUT as shown on Section 10.1.

10.4.2. Turn on the power of all equipment.

10.4.3. Let the EUT work in test mode (Inverter Mode, AC Charge Mode, Solar Charge Mode) and test it.

10.5. Test Procedure

The EUT is placed on a table that is 0.8 meter high above the ground. The EUT is set 3 meters away from the transmitting antenna that is mounted on an antenna tower. Both horizontal and vertical polarization of the antenna is set on test. Each of the four sides of the EUT must be faced this transmitting antenna and measured individually.

In order to judge the EUT performance, a CCD camera is used to monitor it.

All the scanning conditions are as following:

Condition of Test	Remark
1. Fielded Strength	1V/m (Severity Level 1) 3V/m (Severity Level 2)
2. Radiated Signal	Modulated
3. Scanning Frequency	80-2700MHz
4. Sweep time of radiated	0.0015 Decade/s
5. Dwell Time	1 Sec.

10.6. Test Results

PASS.

Please refer to the following pages.

RF Field Strength Susceptibility Test Results

EMTEK (SHENZHEN) CO., LTD.

Applicant	: SHENZHEN SUNRAY POWER CO., LTD			
EUT	: Inverter		Test Date	: June 06, 2019
M/N	: MPS-V-5000-48		Temperature	: 26.5°C
Field Strength	: 3 V/m		Humidity	: 47%
Power Supply	: DC 360V, DC 48V for battery, AC 230V/50Hz		Criterion	: A
Test Mode	: Inverter Mode, AC Charge Mode, Solar Charge Mode		Frequency Range	: 80 MHz to 1000 MHz 1400 MHz to 2000 MHz
Modulation: ☐ None ☐ Pulse ☒ AM 1kHz 80%				
	Frequency Rang 1: 80~ 1000MHz		Frequency Rang 2: 1400~ 2000 MHz	
Steps	1%			
	Horizontal	Vertical	Horizontal	Vertical
Front	A	A	A	A
Right	A	A	A	A
Rear	A	A	A	A
Left	A	A	A	A
Test Equipment : 1. Signal Generator : N5181A (Agilent) 2. Power Amplifier : AS0102-55 (MILMEGA) & 80RF1000-175 (MILMEGA) & AS1860-50 (MILMEGA) 3. Log.-Per.Antenna: VULP9118E (SCHWARZBECK) 4. Broad-Band Horn Antenna: STLP 9149 (Schwarzbeck) 5. RF Power Meter. Dual Channel: 4232A (BOONTON) 6. Field Strength Meter: RSS1006A (DARE)				
Note:				


RF Field Strength Susceptibility Test Results

EMTEK (SHENZHEN) CO., LTD.

Applicant	: SHENZHEN SUNRAY POWER CO., LTD			
EUT	: Inverter		Test Date	: June 06, 2019
M/N	: MPS-V-5000-48		Temperature	: 26.5°C
Field Strength	: 1 V/m		Humidity	: 47%
Power Supply	: DC 360V, DC 48V for battery, AC 230V/50Hz		Criterion	: A
Test Mode	: Inverter Mode, AC Charge Mode, Solar Charge Mode		Frequency Range	: 2000 MHz to 2700 MHz
Modulation: ☐ None ☐ Pulse ☒ AM 1kHz 80%				
	Frequency Rang 1: 2000~ 2700 MHz		Frequency Rang 2: N/A	
Steps	1%			
	Horizontal	Vertical	Horizontal	Vertical
Front	A	A		
Right	A	A		
Rear	A	A		
Left	A	A		
Test Equipment : 1. Signal Generator : N5181A (Agilent) 2. Power Amplifier : AS0102-55 (MILMEGA) & 80RF1000-175 (MILMEGA) & AS1860-50 (MILMEGA) 3. Log.-Per.Antenna: VULP9118E (SCHWARZBECK) 4. Broad-Band Horn Antenna: STLP 9149 (Schwarzbeck) 5. RF Power Meter. Dual Channel: 4232A (BOONTON) 6. Field Strength Meter: RSS1006A (DARE)				
Note:				

11. ELECTRICAL FAST TRANSIENT/BURST IMMUNITY TEST

11.1. Block Diagram of Test Setup



11.2. Test Standard

EN 61000-6-1:2007

(IEC61000-4-4:2012, Severity Level: 2: 1kV, Severity Level: 1: 0.5kV)

11.3. Severity Levels and Performance Criterion

11.3.1. Severity level

Open Circuit Output Test Voltage $\pm 10\%$		
Level	On Power Supply Lines	On I/O (Input/Output) Signal data and control lines
1	0.5 kV	0.25 kV
2	1 kV	0.5 kV
3	2 kV	1 kV
4	4 kV	2 kV
X	Special	Special

11.3.2. Performance criterion: B

11.4. Operating Condition of EUT

11.4.1. Me Setup the EUT as shown on Section 11.1.

11.4.2. Turn on the power of all equipment.

11.4.3. Let the EUT work in test mode (AC Charge Mode, Solar Charge Mode) and test it.

11.5. Test Procedure

The EUT is put on the table that is 0.8meter high above the ground. This reference ground plane shall project beyond the EUT by at least 0.1m on all sides and the minimum distance between EUT and all other conductive structure, except the ground plane beneath the EUT, shall be more than 0.5m.

11.5.1. For input and output AC power ports:

The EUT is connected to the power mains by using a coupling device that couples the EFT interference signal to AC power lines. Both polarities of the test voltage should be applied during compliance test and the duration of the test is 2 mins.

11.5.2. For signal lines and control lines ports:

No I/O ports. It's unnecessary to test.

11.5.3. For DC output line ports:

It's unnecessary to test.

11.6. Test Results

PASS.

Please refer to the following page.


Electrical Fast Transient/Burst Test Results

EMTEK (SHENZHEN) CO., LTD.

Standard: ☒ IEC 61000-4-4		Result: ☒ PASS / ☐ FAIL	
Applicant : <u>SHENZHEN SUNRAY POWER CO., LTD</u>			
EUT : <u>Inverter</u>			
M/N : <u>MPS-V-5000-48</u>			
Input Voltage: <u>DC 360V, AC 230V/50Hz</u>			
Criterion : B			
Ambient Condition : <u>25.7 °C</u> <u>49% RH</u>			
Operation Mode: AC Charge Mode, Solar Charge Mode			
Line : ☒ AC Mains ☒ DC Mains		Line : ☐ Signal ☐ I/O Cable	
Coupling : ☒ Direct		Coupling : ☐ Capacitive	
Test Time : 120s			
Line	Test Voltage	Result(+)	Result(-)
L	1kV	A	A
N	1kV	A	A
PE	1kV	A	A
L、N	1kV	A	A
L、PE	1kV	A	A
N、PE	1kV	A	A
L、N、PE	1kV	A	A
Signal Line			
DC Line	0.5kV	A	A
Note:			

12. SURGE IMMUNITY TEST

12.1. Block Diagram of Test Setup



12.2. Test Standard

EN 61000-6-1:2007

(IEC 61000-4-5:2014, Severity Level: Line to Line: 1.0KV/0.5KV, Line to GND: 2.0KV/1.0KV)

12.3. Severity Levels and Performance Criterion

12.3.1. Severity level

Severity Level	Open-Circuit Test Voltage kV
1	0.5
2	1.0
3	2.0
4	4.0
*	Special

12.3.2. Performance criterion: B

12.4. Operating Condition of EUT

12.4.1. Me Setup the EUT as shown on Section 12.1.

12.4.2. Turn on the power of all equipment.

12.4.3. Let the EUT work in test mode (AC Charge Mode, Solar Charge Mode) and test it.

12.5. Test Procedure

- 1) Set up the EUT and test generator as shown on Section 12.1.2.
- 2) 1.2/50us voltage surge (At open-circuit condition) and 8/20us current surge to EUT selected points.
- 3) At least 5 positive and 5 negative (polarity) tests with a maximum 1/min repetition rate are conducted during test.
- 4) Different phase angles are done individually.
- 5) Record the EUT operating situation during compliance test and decide the EUT immunity criterion for above each test.

12.6.Test Results

PASS.

Please refer to the following page.

Surge Immunity Test Result

EMTEK (SHENZHEN) CO., LTD.

Applicant : SHENZHEN SUNRAY POWER CO., LTD

EUT : Inverter

Test Date : June 06, 2019

M/N : MPS-V-5000-48

Temperature : 25.7°C

Power Supply : DC 360V, AC 230V/50Hz

Humidity : 49%

Test Mode : AC Charge Mode, Solar Charge Mode


Criterion : B

Location	Polarity	Phase Angle	Number of Pulse	Pulse Voltage (kV)	Result
L-N	+	0°/90°	5	1.0	A
	+	180°/270°	5	1.0	A
	-	0°/90°	5	1.0	A
	-	180°/270°	5	1.0	A
L-PE	+	0°/90°	5	2.0	A
	+	180°/270°	5	2.0	A
	-	0°/90°	5	2.0	A
	-	180°/270°	5	2.0	A
N-PE	+	0°/90°	5	2.0	A
	+	180°/270°	5	2.0	A
	-	0°/90°	5	2.0	A
	-	180°/270°	5	2.0	A
P-N	+		5	0.5	A
	-		5	0.5	A
P-PE	+		5	1.0	A
	-		5	1.0	A
N-PE	+		5	1.0	A
	-		5	1.0	A

Remark:

13. INJECTED CURRENTS SUSCEPTIBILITY TEST

13.1. Block Diagram of Test Setup



13.2. Test Standard

EN 61000-6-1:2007

(IEC 61000-4-6:2013, Severity Level: Level 2, 3V (r.m.s.), 0.15MHz ~ 80MHz)

13.3. Severity Levels and Performance Criterion

13.3.1. Severity level

Level	Field Strength V
1	1
2	3
3	10
X	Special

13.3.2. Performance criterion: A

13.4. Operating Condition of EUT

13.4.1. Me Setup the EUT as shown on Section 13.1.

13.4.2. Turn on the power of all equipment.

13.4.3. Let the EUT work in test mode (AC Charge Mode, Solar Charge Mode) and test it.

13.5. Test Procedure

- 1) Set up the EUT, CDN and test generators as shown on Section 13.1.2.
- 2) Let the EUT work in test mode and measure it.
- 3) The EUT are placed on an insulating support 0.1 m high above a ground reference plane. CDN (coupling and decoupling device) is placed on the ground plane about 0.3m from EUT. Cables between CDN and EUT are as short as possible, and their height above the ground reference plane shall be between 30 and 50 mm (where possible).
- 4) The disturbance signal described below is injected to EUT through CDN.
- 5) The EUT operates within its operational mode(s) under intended climatic conditions after power on.
- 6) The frequency range is swept from 150kHz to 80MHz using 3V signal level, and with the disturbance signal 80% amplitude modulated with a 1kHz sine wave.
- 7) The rate of sweep shall not exceed $1.5 \cdot 10^{-3}$ decades/s. where the frequency is swept incrementally; the step size shall not exceed 1% of the start and thereafter 1% of the preceding frequency value.
- 8) Recording the EUT operating situation during compliance testing and decide the EUT immunity criterion.

13.6. Test Results

PASS.

Please refer to the following page.


Injected Currents Susceptibility Test Results

EMTEK (SHENZHEN) CO., LTD.

Applicant : <u>SHENZHEN SUNRAY POWER CO., LTD</u>				
EUT : <u>Inverter</u>		Test Date: <u>June 06, 2019</u>		
M/N : <u>MPS-V-5000-48</u>		Temperature : <u>25.7°C</u>		
Power Supply : <u>DC 360V, AC 230V/50Hz</u>		Humidity : <u>49%</u>		
Test Engineer : <u>LZY</u>				
Test Mode: <u>AC Charge Mode, Solar Charge Mode</u>				
Frequency Range (MHz)	Injected Position	Strength (Unmodulated)	Criterion	Result
0.15 ~ 80	AC Mains	3V	A	A
0.15 ~ 80	DC Mains	3V	A	A
Test Mode : <u>N/A</u>				
Frequency Range (MHz)	Injected Position	Strength (Unmodulated)	Criterion	Result
Remark : 1. Modulation Signal:1kHz 80% AM Measurement Equipment : Simulator: CWS 500C (SWITZERLAND EMTEST) CDN : ☐ CDN-M2 (SWITZERLAND EMTEST) ☒ CDN-M3 (SWITZERLAND EMTEST)		Note:		

14. MAGNETIC FIELD SUSCEPTIBILITY TEST

14.1. Block Diagram of Test Setup



GRP: Ground reference plane
EUT: Equipment under test

14.2. Test Standard

EN 61000-6-1:2007
(IEC 61000-4-8:2009, Severity Level: Level 2, 3A / m)

14.3. Severity Levels and Performance Criterion

14.3.1. Severity Levels

Level	Field Strength A/m
1	1
2	3
3	10
4	30
5	100
X	Special

14.3.2. Performance Criterion: A

14.4. Operating Condition of EUT

14.4.1. Me Setup the EUT as shown on Section 14.1.

14.4.2. Turn on the power of all equipment.

14.4.3. Let the EUT work in test mode (Inverter Mode, AC Charge Mode, Solar Charge Mode) and test it.

14.5. Test Procedure

The EUT is placed in the middle of a induction coil (1*1m), under which is a 1*1*0.8m (high) table, this small table is also placed on a larger table, above the ground. Both horizontal and vertical polarization of the induction coil is set on test, so that each side of the EUT is affected by the magnetic field. Also can reach the same aim by change the position of the EUT.

14.6. Test Results

PASS.

Please refer to the following page.


Magnetic Field Immunity Test Result

EMTEK (SHENZHEN) CO., LTD.

Standard: ☒ IEC 61000-4-8		Result: ☒ PASS / ☐ FAIL		
Applicant : <u>SHENZHEN SUNRAY POWER CO., LTD</u> EUT : <u>Inverter</u> M/N : <u>MPS-V-5000-48</u> Input Voltage : <u>DC 360V, DC 48V for battery,</u> <u>AC 230V/50Hz</u> Date of Test : <u>June 06, 2019</u> Test Engineer: <u>LZY</u> Ambient Condition : Temp : <u>25.7°C</u> Humid: <u>49%</u> Criterion: A				
Operation Mode: Inverter Mode, AC Charge Mode, Solar Charge Mode				
Test Level (A/m)	Testing Duration	Coil Orientation	Criterion	Result
3	5 mins	X	A	A
3	5 mins	Y	A	A
3	5 mins	Z	A	A
Operation Mode: N/A				
Test Level (A/m)	Testing Duration	Coil Orientation	Criterion	Result
Test Equipment	Magnetic Field Test: HEAFELY MAG 100.1			
Note:				

15. VOLTAGE DIPS AND INTERRUPTIONS TEST

15.1. Block Diagram of Test Setup



15.2. Test Standard

EN 61000-6-1:2007 (IEC 61000-4-11:2004)

15.3. Severity Levels and Performance Criterion

15.3.1. Severity level

Test Level %UT	Voltage dip and short interruptions %UT	Duration (in period)
0	100	0.5 1 5
70	30	10 25 50
0	100	*

15.3.2. Performance criterion: B&C

15.4. Operating Condition of EUT

15.4.1. Me Setup the EUT as shown on Section 15.1.

15.4.2. Turn on the power of all equipment.

15.4.3. Let the EUT work in test mode (AC Charge Mode) and test it.

15.5. Test Procedure

- 1) Set up the EUT and test generator as shown on Section 15.1.2.
- 2) The interruption is introduced at selected phase angles with specified duration.
- 3) Record any degradation of performance.

15.6. Test Results

PASS.

Please refer to the following page.

Voltage Dips and Interruptions Test Results

EMTEK (SHENZHEN) CO., LTD.

Applicant : SHENZHEN SUNRAY POWER CO., LTD

EUT : Inverter

Test Date : June 06, 2019

M/N : MPS-V-5000-48

Temperature : 25.7°C

Power Supply : AC 230V/50Hz

Humidity : 49%

Test Mode: AC Charge Mode

Test Level % U_T	Voltage Dips & Short Interruptions % U_T	Duration (in periods)	Criterion ☐ A ☒ B ☒ C ☐ D	Result
0	100	0.5P	B	A
0	100	1P	B	A
70	30	25P	C	A
0	100	250P	C	B

Test Mode : N/A

Test Level % U_T	Voltage Dips & Short Interruptions % U_T	Duration (in periods)	Criterion ☐ A ☐ B ☐ C ☐ D	Result


Note: Dips to 0%, Duration 250P, EUT stopped operation, but it can be resumed by itself after test.

16. PHOTOGRAPHS

16.1. Photos of Conducted Emission Measurement



16.2.Photos of Radiation Emission Measurement



16.3.Photo of Harmonic / Flicker Measurement



16.4.Photo of Electrostatic Discharge Test



16.5.Photo of RF Field Strength Susceptibility Test




16.6.Photo of Electrical Fast Transient / Burst Test



16.7.Photo of Surge Test



16.8.Photo of Injected Currents Susceptibility Test



16.9.Photo of Magnetic Field Immunity Test





16.10.Photo of Voltage Dips and Interruption Immunity Test



APPENDIX (Photos of EUT)







-----The end-----